

Engineered for strength, durability, and performance, our synthetic ropes are designed to meet the toughest demands in marine and heavy industrial applications.

3 strands of high-tenacity co-polymer rope twisted together, offering strength, durability, and flexibility.

This rope is used in rigging, oil fields, fishing, shellfish, aquaculture, fish farming, and industrial applications.



KEY FEATURES

Strong yet flexible, good abrasion resistance.

Diameter (mm)	Diameter (in)	Weight (lbs/100 ft)	Weight (kgs/100 m)	Minimum Breaking Strength (kgf)	Minimum Breaking Strength (lbs)
6	1/4	1.14	1.70	680	1,499
8	5/16	2.02	3.00	1,200	2,646
10	3/8	3.06	4.55	1,800	3,968
12	1/2	4.43	6.59	2,700	5,952
14	9/16	6.05	9.00	3,600	7,937
16	5/8	7.79	11.59	4,500	9,921
18	3/4	9.95	14.80	5,800	12,787
20	13/16	12.10	18.00	6,900	15,212
24	1	17.47	26.00	9,900	21,826
28	1-1/8	23.85	35.50	13,200	29,101
32	1-5/8	30.91	46.00	16,800	37,038
36	1-7/16	39.31	58.50	20,600	45,415
40	1-5/8	48.38	72.00	25,700	56,659
48	2	69.88	104.00	36,600	80,689
56	2-1/4	95.42	142.00	52,000	114,640
60	2-1/2	109.53	163.00	59,500	131,750