

### FEATURES & BENEFITS

- High strength galvanized steel hardware with a tested safe working load of 15,000 lbs / 6,804 kg providing superior strength and corrosion resistance
- Highest quality UV stabilized seamless one-piece construction with uniform wall thickness ensures a robust life expectancy to 15+ years
- Large diameter load plates secured to the shell for maximum load disbursement
- Refined EPS foaming process with over 20 years of experience significantly reduces risk of sinking and environmental contamination
- Swivel eyes prevent twisting and moderate strain on the tackle
- Indented area for retro-reflective tape inhibits sliding and loss of reflective material
- 3M™ Flexible Prismatic Reflective 4" wide yellow tape applied as standard

### GENERAL SPECIFICATIONS

|                |                   |
|----------------|-------------------|
| Diameter       | 36" / 914 mm      |
| Wall Thickness | 1/4" / 6mm        |
| Overall Height | 46' / 1171 mm     |
| Air Weight     | 77 lbs / 35 kg    |
| Net Buoyancy   | 1500 lbs / 680 kg |

### AVAILABLE OPTIONS

- Reflective Banding
- Custom Colours

### MATERIAL SPECIFICATIONS

#### POLYETHYLENE

Virgin PE material with a UV 15 inhibitor

#### COLOUR

Comes in standard yellow

#### EPS FOAM

1 lb/ft.<sup>3</sup> / 16 kg/m<sup>3</sup> density closed cell EPS

#### STAINLESS STEEL

Inserts are made with a minimum rating of 18-8 stainless steel steel

#### GALVANIZED STEEL

Internal components are hot-dipped galvanized

